



Special cleaning-systems for
the food and nonfood industry

Smoke stick washing machine

KRS 500



**With our smoke stick KRS 500
washing machine 500 sticks
can be cleaned in one wash-cycle.**

**The intelligent control saves time and costs.
The system works fully automatic.
Only the needed amount of cleaning detergent is being added.**

Your advantages at a glance:

- Amortisation of investment costs after shortest time
- Extreme time saving (only still 10 minutes work input)
- The optimized, fully automatic cleaning cycle, as well as the clever practice details guarantee a perfect cleaning result.
- Cleaning detergent can be pumped directly out of the container or can be filled by hand.
- Saving of cleaning detergent through dirt depending dosing
- 2 cleaning programs (heavy and normal soiling)
- Integrated heating (temperature is maintained on optimum level)
- Perfect working height through comfortable ergonomometry
- Low operating and maintenance costs



Special cleaning-systems for the food and nonfood industry

Smoke stick washing machine

KRS 500

Technical data

Type	Top-Clean	Easy-Clean
cleaning capacity	500 smoke sticks per cleaning cycle	500 smoke sticks per cleaning cycle
cleaning cycle	fully automatic	half automatic
max. smoke stick length	1000 mm	1000 mm
cleaning programs	2 cleaning programs for normal and heavy soiling are pre-programmed and with a touch of a button available	2 cleaning programs for normal and heavy soiling are pre-programmed and with a touch of a button available
electric connection	400 Volt/ 50 Hz/ 16 Ampere/ 6,5 kW	400 Volt/ 50 Hz/ 16 Ampere/ 6,5 kW
compressed air conn.	4 , 5 - 10 bar	not applicable
water connection	3/4 inch warm water with 50-55°C	3/4 inch warm water with 50-55°C
maintain heating for water tank	6 kW electric heating with individual temperature control	6 kW electric heating with individual temperature control
water consumption per cleaning cycle	ca.300 Liter, depending on amount of sticks	ca.300 Liter, depending on amount of sticks
detergent consumption	intensity is adjustable via dosing device and conductivity sensor	manually filling
function surveillance control	eventually errors are displayed. Top-Clean shuts off automatically	not available



KERRES
anlagensysteme

KERRES Anlagensysteme GmbH
Manfred-von-Ardenne-Allee 11
D-71522 Backnang
Fon +49 (0) 7191 9129-0
Fax +49 (0) 7191 9129-70
www.kerres-group.de
info@kerres-group.de

